

REMARKS

The Specification has been amended to incorporate the continuity and to correct minor typographical errors. Claim 1 has been amended to correct a minor typographical error. Claims 8, and 10 have been amended to delete the multiple dependency. The Abstract has been amended to correct a minor typographical error. No new matter has been introduced. Entry of this amendment is respectfully solicited.

Respectfully submitted,

McDERMOTT WILL & EMERY LLP


Michael E. Fogarty
Registration No. 36,139

600 13th Street, N.W.
Washington, DC 20005-3096
Phone: 202.756.8000 MEF:sln
Facsimile: 202.756.8087
Date: March 10, 2006

**Please recognize our Customer No. 20277
as our correspondence address.**

JP2004-070770 10 MAR 2006

DESCRIPTION

IMAGING LENS, IMAGING UNIT, AND OPTICAL DEVICE

5 --RELATED APPLICATION

This application is a national phase of PCT/JP2004/013566 filed on September 10, 2004, which claims priority from Japanese Application No. 2003-318012 filed on September 10, 2003, the disclosures of which Applications are incorporated by reference
10 herein. The benefit of the filing and priority dates of the International and Japanese Applications is respectfully requested.--

TECHNICAL FIELD

The present invention relates to an imaging lens system,
15 a compact imaging unit using a solid-state image sensor such as a CCD or a CMOS, and an optical device such as a digital still camera or a compact camera used in a personal digital assistance.

BACKGROUND ART

20 Recently, as a digital still camera (hereinafter, referred to as a DSC) or the like has rapidly gained popularity, imaging lenses with high optical performance compatible with a large number of pixels equal to or more than five million pixels have been commercialized for use in an image input device recording a digital
25 image. In addition, many mobile telephones or PDA terminals

provided with a compact camera have been commercialized, and accepted in the marketplace. Among them, compact imaging units and imaging lenses compatible with a large number of pixels (two million to four million pixels) equivalent to that of a DSC are particularly gaining attention for use in, for example, compact cameras provided in mobile terminals or the like, in particular.

Conventional downsized imaging units and imaging lenses can be largely divided into two groups.

One is imaging lenses used mainly in mobile telephones for which downsizing and cost reduction are sought, PC (personal computer) cameras, PDAs, or the like, as disclosed in Japanese Laid-Open Patent Publication No. 2003-195158, for example. These are highly attractive in their sizes and costs and thereby commercialized in a large number, but not compatible with a large number of pixels, and, in many cases, they are only compatible with about one hundred thousand to three hundred fifty thousand pixels. A compact image sensor having an image quality of more than one million pixels is proposed, as disclosed in Japanese Laid-Open Patent Publication No. 2003-149547, for example. However, the number of lenses therein is as many as four or more, and a less expensive, compact type is sought for portability.

The other is in a field applied in endoscopes, surveillance cameras, or the like. The lenses achieve high optical performance and downsizing of some extent. However, the number of lenses therein is as many as six to nine to ensure the required performance,

and portability and cost thereof do not allow a common use.

DISCLOSURE OF THE INVENTION

In the above imaging unit and the imaging lens, in order
5 to achieve a favorable optical performance while adopting an
inexpensive configuration and trying to downsize its entire lens
system, the lens shape or the like need to be appropriately
configured while keeping the number of lenses to a minimum.

Generally, in order to downsize, an optical power of lenses
10 is increased. However, when the optical power of the lenses is
increased, aberration occurred in each of the lenses becomes large,
thereby causing a problem that favorable aberration compensation
in the entire optical system is difficult.

The object of the present invention is to provide, by
15 employing an imaging lens configured with three, as the minimum
number, lenses, and adopting an appropriate configuration for each
of the lenses, the imaging lens and an optical device for which
an entire lens system is downsized and a high optical performance
is obtained.

20 In order to solve the above problem, the present invention
provides an imaging lens system for forming an optical image of
an object on a light receiving surface of a solid-state image sensor;
comprising, in order from an object side: an aperture diaphragm,
and three lens elements, i.e., a first lens element which is a
25 bi-aspherical lens having a positive optical power and a convex

surface on an image side, a second lens element having a negative optical power and being a bi-aspherical meniscus lens whose object side has a concave shape and a third lens element having a positive optical power and being a bi-aspherical meniscus lens whose object
5 side has a convex shape; and satisfying the following conditional expressions:

$$1.5 < |fd/f2d| < 2.3 \quad (1)$$

$$0.5 < |fd/f3d| < 1.1 \quad (2)$$

$$-2.2 < (r_{21}+r_{22})/(r_{21}-r_{22}) < -1.3 \quad (3)$$

$$10 \quad \cancel{2.1} \text{ } \underline{-2.1} < (r_{31}+r_{32})/(r_{31}-r_{32}) < -1.7 \quad (4)$$

here,

fd is a composite focal length of an entire imaging lens system to d-line (mm),

f2d is a focal length of the second lens element to the d-line
15 (mm),

f3d is a focal length of the third lens element to the d-line (mm),

r₂₁ is a radius of curvature of an object side surface of the second lens element (mm),

20 r₂₂ is a radius of curvature of an image side surface of the second lens element (mm),

r₃₁ is a radius of curvature of an object side surface of the third lens element (mm), and

r_{32} is a radius of curvature of an image side surface of the third lens element (mm).

BRIEF DESCRIPTION OF THE DRAWINGS

5 FIG. 1 is a schematic configuration diagram of an imaging lens according to Embodiment 1 of the present invention.

FIG. 2 is an aberration diagram of the imaging lens according to Embodiment 1 of the present invention.

10 FIG. 3 is a schematic configuration diagram of an imaging lens according to Embodiment 2 of the present invention.

FIG. 4 is an aberration diagram of the imaging lens according to Embodiment 2 of the present invention.

FIG. 5 is a schematic configuration diagram of an imaging lens according to Embodiment 3 of the present invention.

15 FIG. 6 is an aberration diagram of the imaging lens according to Embodiment 3 of the present invention.

FIG. 7 is a schematic configuration diagram of an imaging lens according to Embodiment 4 of the present invention.

20 FIG. 8 is an aberration diagram of the imaging lens according to Embodiment 4 of the present invention.

FIG. 9 is a schematic configuration diagram of an imaging lens according to Embodiment 5 of the present invention.

FIG. 10 is an aberration diagram of the imaging lens according to Embodiment 5 of the present invention.

25 FIG. 11 is a schematic configuration diagram of an imaging

lens according to Embodiment 6 of the present invention.

FIG. 12 is an aberration diagram of the imaging lens according to Embodiment 6 of the present invention.

FIG. 13 is a schematic configuration diagram of an imaging
5 lens according to Embodiment 7 of the present invention.

FIG. 14 is an aberration diagram of the imaging lens according to Embodiment 7 of the present invention.

FIG. 15 is a schematic configuration diagram of an imaging lens according to Embodiment 8 of the present invention.

10 FIG. 16 is an aberration diagram of the imaging lens according to Embodiment 8 of the present invention.

FIG. 17 is a schematic configuration diagram of an imaging lens according to Embodiment 9 of the present invention.

15 FIG. 18 is an aberration diagram of the imaging lens according to Embodiment 9 of the present invention.

FIG. 19 is a schematic diagrammatic perspective view of an optical device showing an embodiment of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

20 Hereinafter, an embodiment of the present invention is described.

FIGS. 1, 3, 5, 7, 9, 11, 13, 15, and 17 are schematic configuration diagrams illustrating imaging lenses according to Embodiments 1, 2, 3, 4, 5, 6, 7, 8, and 9 of the present invention,
25 respectively.

In each of the diagrams, in order from an object side, 100 denotes an aperture diaphragm, 101 denotes a first lens element (hereinafter, refers to as an "L1"), 102 denotes a second lens element (hereinafter, refers to as an "L2"), 103 denotes a third lens element (hereinafter, refers to as an "L3"), 104 denotes an optical low-pass filter (hereinafter, refers to as an "OLPF"), 105 denotes an image plane, and 106 denotes a solid-state image sensor such as a CCD or a CMOS.

In the above configuration, an imaging lens system includes the aperture diaphragm 100, the first lens element L1, the second lens element L2, and the third lens element L3, and an imaging unit includes the imaging lens system and the solid-state image sensor 106.

The first lens element L1, the second lens element L2, and the third lens element L3 are all lenses having aspherical surfaces on both faces. The shapes of these aspherical surfaces are represented by the following expression.

$$Z = \frac{(1/CR) \cdot H^2}{1 + \sqrt{1 - (1+K) \cdot (1/CR)^2 \cdot H^2}} + \sum_{n=4}^{16} A_n \cdot H^n$$

Here, in a cylindrical coordinate system including a Z axis referring to an axis extending toward an image plane side along an optical axis direction, and an H axis referring to an axis vertically extending along a direction away from the optical axis; CR is a paraxial radius of curvature (mm), K is a conic coefficient, and A_n is an n-th order aspherical coefficient.

The first lens element L1 is a lens, formed by a glass material or from a synthetic resin material, of aspherical surfaces on both faces, and having a positive optical power. The second lens element L2 is a lens, formed from the synthetic resin material, of aspherical surfaces on both faces, and having a negative optical power. The third lens element L3 is a lens, formed from the synthetic resin material, of aspherical surfaces on both faces, and having a positive optical power.

In order to obtain a compact body and a favorable image quality for the imaging lens system according to each of the embodiments, power of the second lens element L2 and the third lens element L3 need to be designed with appropriate values, and bending shape thereof also need to be designed with appropriate values. For this reason, it is preferable that the following conditional expressions are satisfied.

$$1.5 < |f_d/f_{2d}| < 2.3 \quad (1)$$

$$0.5 < |f_d/f_{3d}| < 1.1 \quad (2)$$

$$-2.2 < (r_{21}+r_{22})/(r_{21}-r_{22}) < -1.3 \quad (3)$$

$$-2.1 < (r_{31}+r_{32})/(r_{31}-r_{32}) < -1.7 \quad (4)$$

Here,

f_d is a composite focal length of the entire lens system to d-line (mm),

f_{2d} is a focal length of the second lens element L2 to the d-line (mm),

f_{3d} is a focal length of the third lens element L3 to the

d-line (mm),

r_{21} is a radius of curvature of an object side surface of the second lens element L2 (mm),

r_{22} is a radius of curvature of an image side surface of the second lens element L2 (mm),

r_{31} is a radius of curvature of an object side surface of the third lens element L3 (mm), and

r_{32} is a radius of curvature of an image side surface of the third lens element L3 (mm).

10 The above conditional expression (1) indicates the power of the second lens element L2 with respect to power of the entire lens system. When the lower limit of the expression is exceeded, chromatic aberration is insufficiently compensated, causing difficulties in obtaining a favorable image quality. Also, when
15 the upper limit thereof is exceeded, the amount of aberration occurrence in a single lens corresponding to the second lens element L2 becomes excessively large, causing difficulties in obtaining a favorable image quality in the entire lens system.

20 The conditional expression (2) indicates the power of the third lens element L3 with respect to the power of the entire lens system. When the lower limit of the expression is exceeded, a position of principal points for the entire lens system becomes excessively close to the image side, causing difficulties in downsizing and in obtaining a favorable image quality. Also, when
25 the upper limit thereof is exceeded, the amount of aberration

occurrence in a single lens corresponding to the third lens element L3 becomes excessively large, causing difficulties in obtaining a favorable image quality in the entire lens system, and simultaneously, the tilt angle of a surface in the neighborhood
5 of an effective diameter of the image side surface r_{32} of the third lens element L3 becomes excessively large, causing difficulties in manufacturing thereof.

The conditional expression (3) represents a shape factor indicating a bending shape of the second lens element L2. When
10 the lower limit of the expression is exceeded, spherical aberration due to the object side surface r_{21} thereof occurs in a large amount, and, when the upper limit thereof is exceeded, astigmatism due to the image side surface r_{22} of the second lens element L2 occurs in a large amount, causing difficulties in obtaining a favorable
15 quality in either case.

The conditional expression (4) represents a shape factor indicating a bending shape of the third lens element L3. When the lower limit of the expression is exceeded, astigmatism occurs in a large amount, and, when the upper limit thereof is exceeded,
20 spherical aberration due to the image side surface r_{32} of the third lens element L3 occurs in a large amount, causing difficulties in obtaining a favorable quality in either case.

More preferably, in consideration of lens manufacturing, it is preferable that the tilt angle of a surface θ_{32} in the
25 neighborhood of the effective diameter of the image side surface

r_{32} of the third lens element L3 satisfies the following conditional expression (13).

$$\theta_{32} < 67 \text{ (unit: in degrees)} \quad (13)$$

When the above θ_{32} exceeds the upper limit of the conditional expression (13), it is advantageous for distortion compensation and astigmatism compensation, however, not only precision for the shape of the aspherical surfaces is reduced, but also precision for shape management is reduced, thereby causing difficulties in stably producing lenses.

As for the entire lens system, in order to achieve downsizing and a favorable image quality, an angle of view ($2\omega_d$) and an entire length of the lens system are required to be set to appropriate values. When the angle of view is set wide, a focal length is shortened, and therefore, it is advantageous for downsizing. However, aberration compensation has to be favorably performed at wide angle of view, and particularly, compensation for astigmatism or distortion is difficult.

On the other hand, when the angle of view is set narrow, the focal length needs to be set long, and therefore, it is disadvantageous when requiring downsizing, but astigmatism or distortion is easily compensated.

Consequently, it is preferable that the imaging lens system according to each of the embodiments satisfies the following conditional expressions to achieve downsizing in the entire lens system and a favorable image quality.

$$60 < 2 \cdot \omega d < 70 \quad (5)$$

$$1.2 < T/fd < 1.7 \quad (6)$$

Here,

ωd is a half view angle of the entire lens system to the
5 d-line (unit: in degrees), and

T is an entire length between the object side surface r_{11}
of the first lens element $L1$ and the image plane ~~106~~ 105 (mm).

In the above conditional expression (5), a usual standard
angle of view is set (about 35 mm using a 135 film camera).

10 In a case of downsizing the entire length of the entire lens
system, the most favorable image quality is obtained by satisfying
the above condition. When the ωd exceeds the upper limit of the
above condition, the angle of view becomes narrow, and the focal
length becomes long thereby lengthening the entire length.
15 Therefore, downsizing cannot be achieved. When the ωd exceeds
the lower limit thereof, the angle of view becomes excessively
wide. Therefore, astigmatism and distortion cannot be
compensated.

The conditional expression (6) is an expression indicating
20 the ratio between the entire length of the above lens system and
the focal length of the entire lens system. In order to achieve
downsizing and a favorable image quality, this conditional
expression needs to be satisfied. When the lower limit of the
condition is exceeded, aberration on each of the lens surfaces
25 occurs in a large amount, and therefore, a favorable image quality

as a whole cannot be obtained. When the upper limit thereof is exceeded, downsizing cannot be achieved, thereby resulting in a less attractive imaging lens system.

In the imaging lens system according to each of the
5 embodiments, in order to obtain a compact body and a favorable image quality, the power of the first lens element L1 needs to be designed with an appropriate value, and the bending shape also needs to be designed with an appropriate value.

Therefore, it is preferable that the following conditional
10 expressions are satisfied.

$$1.4 < |f_d/f_{ld}| < 2.0 \quad (7)$$

$$0.3 < (r_{11}+r_{12})/(r_{11}-r_{12}) < 0.7 \quad (8)$$

Here,

f_{ld} is a focal length of the first lens element L1 to the
15 d-line (mm),

r_{11} is a radius of curvature of the object side surface of the first lens element L1 (mm), and

r_{12} is a radius of curvature of the image side surface of the first lens element L1 (mm).

20 The above conditional expression (7) indicates the power of the first lens element L1 with respect to the power of the entire lens system. When the lower limit of the expression is exceeded, a position of paraxial exit pupil for the entire lens system becomes excessively close to an image side, whereby an incident angle of
25 an off-axial principal ray onto the image plane 105 cannot be reduced.

When the upper limit thereof is exceeded, the amount of aberration occurrence in a single lens corresponding to the first lens element L1 becomes excessively large, and simultaneously, the tilt angle of a surface in the neighborhood of an effective diameter of the image side surface r_{12} of the first lens element L1 becomes
5 excessively large, thereby causing difficulties in manufacturing thereof. In consideration of the lens manufacturing, more preferably, it is preferable that the tilt angle of a surface θ_{12} in the neighborhood of the effective diameter of the image side surface r_{12} of the first lens element L1 satisfies the following
10 conditional expression (14).

Also, the above conditional expression (8) represents a shape factor indicating a bending shape of the first lens element L1. When the lower limit of the expression (8) is exceeded, spherical
15 aberration and astigmatism at a high position of an image height occur in a large amount, and, when the upper limit thereof is exceeded, coma aberration occurs in a large amount, thereby causing difficulties in obtaining a favorable quality in either case.

$$\theta_{12} < 56 \text{ (unit: in degrees)} \quad (14)$$

20 In the conditional expression (14), when the θ_{12} exceeds the upper limit thereof, it is advantageous for distortion compensation and astigmatism compensation, however, not only precision for the shape of the aspherical surfaces is reduced, but also precision for shape management is reduced, thereby causing
25 difficulties in stably producing lenses.

Also, in the second lens element L2 and the third lens element L3, it is preferable to have, in their effective diameters, at least one point taking a value of zero for a first-order differential of Z with respect to H (dZ/dH), where Z is depicted in the following
5 expression indicating an aspherical surface.

$$Z = \frac{(1/CR) \cdot H^2}{1 + \sqrt{1 - (1+K) \cdot (1/CR)^2 \cdot H^2}} + \sum_{n=4}^{16} A_n \cdot H^n$$

Here, in a cylindrical coordinate system including: a Z axis referring to an axis extending toward an image plane side along an optical axis direction; and an H axis referring to an axis
10 vertically extending along a direction away from the optical axis, CR is a paraxial radius of curvature (mm), K is a conic coefficient, and A_n is an n-th order aspherical coefficient.

In the second lens element L2 and the third lens element L3, when at least one point taking a value of zero for the dZ/dH
15 is provided in the effective diameters, distortion is favorably compensated, and the incident angle of the off-axial principal ray onto the image plane 105 is advantageously reduced. Also, through reducing the incident angle of the off-axial principal ray onto the image plane 105, shading causing an illuminance
20 reduction is effectively reduced.

Also, in the second lens element L2 and the third lens element L3, in order for chromatic aberration and a curvature of field, as a whole, to be compensated in a favorably well balanced manner, it is preferable that each of Abbe numbers satisfies the following

conditional expressions.

$$25 < V2d < 35 \quad (9)$$

$$50 < V3d < 60 \quad (10)$$

The Abbe number refers to a value calculated from refractive
5 indices to d-line (587.56nm), F-line (486.13nm), and C-line
(656.27nm), and is represented by the following expression.

$$V_d = \frac{(N_d - 1)}{(N_f - N_c)}$$

Here, N_d , N_f , N_c are refractive indices to d-line, F-line, and
C-line, respectively.

10 The above conditional expressions (9) and (10) respectively
designate the Abbe numbers of a material for the second lens element
L2 and the third lens element L3. In the conditional expression
(9), when $V2d$ exceeds the lower limit thereof, chromatic aberration
is favorably compensated, but a Petzval sum for the entire lens
15 system becomes excessively large whereby the curvature of field
becomes large, and, when $V2d$ exceeds the upper limit thereof, the
chromatic aberration is insufficiently compensated, and
simultaneously, the power of each lens is required to be more
increased, whereby the amount of aberration occurring in a single
20 lens becomes excessively large, causing difficulties in obtaining
a favorable image quality in either case.

In the above conditional expression (10), when $V3d$ exceeds
the lower limit thereof, chromatic aberration of magnification,

in particular, occurs in a large amount, and, when V3d exceeds the upper limit thereof, the chromatic aberration of magnification is excessively compensated, and simultaneously, the Petzval sum for the entire lens system becomes large whereby the curvature of field becomes large, causing difficulties in obtaining a favorable image quality in either case.

Also, it is preferable that the first lens element L1 satisfies the following conditional expression (11) in order for the chromatic aberration as a whole to be favorably compensated.

10 $50 < V1d < 65$ (11)

The above conditional expression (11) designates an Abbe number of a material for the first lens element L1. When the lower limit of the conditional expression (11) is exceeded, axial chromatic aberration is insufficiently compensated, and, when the upper limit thereof is exceeded, chromatic aberration can be favorably compensated, but the Petzval sum becomes large whereby the curvature of field becomes large, causing difficulties in obtaining a favorable image quality in either case.

The aperture diaphragm 100 is positioned on a side closest to an object, and therefore, the incident angle of the off-axial principal ray onto the image plane 105 can be reduced, and shading causing an illuminance reduction is effectively reduced.

Also, in order to achieve downsizing for the lenses, it is preferable that the incident angle is maintained in a reasonable range, and therefore, it is desired to set an appropriate value

to the incident angle of the off-axial principal ray.

Therefore, more preferably, it is preferable that the maximum incident angle of the off-axial principal ray onto the image plane 105 (θ_{\max}) satisfies the following conditional expression (12).

5 $10 < \theta_{\max} < 25$ (unit: in degrees) (12)

In the above conditional expression (12), when the θ_{\max} exceeds the lower limit thereof, the entire lens system cannot be downsized, and, when the θ_{\max} exceeds the upper limit thereof, shading becomes large, thereby substantially reducing ambient
10 illuminance.

The OLPF 104 is constructed with a material having birefringent characteristics, such as a crystal. The solid-state image sensor 106 such as a CCD takes an object image, formed by the imaging lens, as a two dimensional sampling image having a
15 low numerical aperture. Therefore, high frequencies equal to or more than half of sampling frequency become false signals. In order to eliminate such high frequency components of an image in advance, it is preferable that the OLPF 104 is positioned between the third lens element L3 and the image plane 105.

20 Also, more preferably, because the solid-state image sensor 106 is generally highly sensitive to light in the infrared region, in order to have natural color reproduction, the OLPF 104 is preferably provided with an IR cut function for filtering out the light in the infrared region, by providing an IR absorbing material
25 or coating.

Hereinafter, concrete numeral data corresponding to Embodiments 1 to 9 are shown as Numerical examples 1 to 9.

(Numerical example 1)

Surface number	Radius of curvature R d	Distance d	Refractive index n _d	Abbe number v _d
1	INF	0.35		
2	4.89911	1.152	1.60602	57.5
3	-2.08542	0.6618		
4	-0.95475	0.987	1.58387	30.9
5	-4.51679	0.3675		
6	2.23064	2.1594	1.53116	56.0
7	6.60981	0.3		
8	INF	0.43	1.51633	64.1
9	INF	0		

A spherical coefficient

Surface number	K	A4	A6	A8	A10	A12	A14	A16
2	2.58408E+01	-6.84156E-02	-6.21333E-02	1.07211E-02	-9.07655E-02	1.35421E-02	1.17743E-01	-1.68189E-01
3	1.33811E+00	-2.70276E-02	-1.35115E-02	-9.19301E-03	1.44867E-02	-1.70906E-03	-6.42628E-03	2.30094E-03
4	-8.70576E-01	1.31794E-01	-4.89178E-02	-4.57772E-02	1.71945E-01	-1.90392E-01	9.95169E-02	-2.01315E-02
5	3.44373E+00	1.75856E-02	1.53343E-02	1.02894E-02	-6.70791E-03	-2.17982E-04	9.16302E-04	-1.74721E-04
6	-8.44035E+00	-6.94865E-03	2.98410E-04	2.78163E-04	-6.31408E-05	4.89103E-06	-9.36535E-08	-2.19446E-08
7	-3.42779E+00	-1.79099E-02	2.36410E-03	-5.19999E-04	5.68945E-05	-2.98338E-06	1.42863E-07	-1.05161E-08

(Numerical example 2)

Surface number	Radius of curvature R d	Distance d	Refractive index n _d	Abbe number v _d
1	INF	0.35		
2	4.89911	1.152	1.60602	57.5
3	-2.08542	0.6618		
4	-0.95813	1.0269	1.58387	30.9
5	-4.5325	0.3363		
6	2.25852	2.1588	1.53116	56.0
7	6.6461	0.3		
8	INF	0.43	1.51633	64.1
9	INF	0		

A spherical coefficient

Surface number	K	A4	A6	A8	A10	A12	A14	A16
2	2.58408E+01	-6.84156E-02	-6.21334E-02	1.07210E-02	-9.07655E-02	1.35422E-02	1.17743E-01	-1.68189E-01
3	1.33811E+00	-2.70276E-02	-1.35115E-02	-9.19300E-03	1.44867E-02	-1.70906E-03	-6.42628E-03	2.30094E-03
4	-8.70591E-01	1.31839E-01	-4.89233E-02	-4.59445E-02	1.71757E-01	-1.90481E-01	9.95151E-02	-2.00899E-02
5	3.47582E+00	1.77139E-02	1.52622E-02	1.02421E-02	-6.72504E-03	-2.21724E-04	9.16884E-04	-1.73322E-04
6	-8.50891E+00	-6.72094E-03	3.35327E-04	2.67567E-04	-6.40441E-05	4.91179E-06	-7.78488E-08	-1.88608E-08
7	-2.05058E+00	-1.78476E-02	2.25532E-03	-5.22183E-04	5.74739E-05	-2.94368E-06	1.43928E-07	-1.05904E-08

(Numerical example 3)

Surface number	Radius of curvature R,d	Distance d	Refractive index n _d	Abbe number v _d
1	INF	0.35		
2	4.89911	1.152	1.60602	57.5
3	-2.08542	0.6618		
4	-0.9582	1.0272	1.58387	30.9
5	-4.53286	0.336		
6	2.24956	2.2162	1.53116	56.0
7	6.57816	0.3		
8	INF	0.43	1.51633	64.1
9	INF	0		

Aspherical coefficient

Surface number	K	A ₄	A ₆	A ₈	A ₁₀	A ₁₂	A ₁₄	A ₁₆
2	2.58408E+01	-6.84156E-02	-6.21334E-02	1.07210E-02	-9.07655E-02	1.35422E-02	1.17743E-01	-1.68189E-01
3	1.33811E+00	-2.70276E-02	-1.35115E-02	-9.19300E-03	1.44867E-02	-1.70906E-03	-6.42628E-03	2.30094E-03
4	-8.70481E-01	1.31820E-01	-4.89328E-02	-4.59531E-02	1.71754E-01	-1.90477E-01	9.95204E-02	-2.00904E-02
5	3.47671E+00	1.77170E-02	1.52602E-02	1.02408E-02	-6.72558E-03	-2.21879E-04	9.16894E-04	-1.73257E-04
6	-8.37097E+00	-6.17947E-03	5.63553E-04	2.28399E-04	-6.18810E-05	5.00436E-06	-9.86419E-08	-1.25937E-08
7	-2.93906E+00	-1.65471E-02	2.09079E-03	-4.91484E-04	5.77343E-05	-3.23446E-06	1.25237E-07	-6.90898E-09

(Numerical example 4)

Surface number	Radius of curvature R d	Distance d	Refractive index n _d	Abbe number v _d
1	INF	0.35		
2	5.13176	1.1858	1.60602	57.5
3	-2.0626	0.6495		
4	-0.95563	0.9102	1.58387	30.9
5	-4.58256	0.3929		
6	2.19872	2.0549	1.53116	56.0
7	7.86594	0.3		
8	INF	0.43	1.51633	64.1
9	INF	0		

A spherical coefficient

Surface number	K	A ₄	A ₆	A ₈	A ₁₀	A ₁₂	A ₁₄	A ₁₆
2	2.58465E+01	-6.53643E-02	-5.70615E-02	5.12728E-03	-1.00546E-01	1.01476E-02	1.27524E-01	-1.43226E-01
3	1.35899E+00	-2.84020E-02	-1.37565E-02	-8.67808E-03	1.46609E-02	-2.02273E-03	-6.68782E-03	2.46902E-03
4	-8.59214E-01	1.29496E-01	-4.83813E-02	-4.65824E-02	1.70338E-01	-1.90674E-01	1.00189E-01	-2.02053E-02
5	3.54447E+00	1.75573E-02	1.51694E-02	1.01856E-02	-6.75128E-03	-2.34773E-04	9.13041E-04	-1.71567E-04
6	-7.61925E+00	-9.00511E-03	6.82672E-04	1.87463E-04	-6.52365E-05	4.93797E-06	-7.56399E-08	-7.47629E-09
7	2.31319E+00	-1.59024E-02	1.73506E-03	-5.04314E-04	5.83937E-05	-3.22142E-06	1.22810E-07	-7.29160E-09

(Numerical example 5)

Surface number	Radius of curvature R d	Distance d	Refractive index n _d	Abbe number v _d
1	INF	0.35		
2	4.89864	1.1632	1.60602	57.5
3	-2.10663	0.6586		
4	-0.95927	0.9151	1.58387	30.9
5	-4.74767	0.4043		
6	2.22455	2.1242	1.53116	56.0
7	8.24416	0.3		
8	INF	0.43	1.51633	64.1
9	INF	0		

Aspherical coefficient

Surface number	K	A ₄	A ₆	A ₈	A ₁₀	A ₁₂	A ₁₄	A ₁₆
2	2.56578E+01	-6.51569E-02	-6.19700E-02	3.22834E-03	-9.17943E-02	3.03517E-02	1.30271E-01	-1.88547E-01
3	1.34723E+00	-2.89314E-02	-1.32113E-02	-8.12905E-03	1.45408E-02	-2.42841E-03	-6.94103E-03	2.93831E-03
4	-8.63825E-01	1.30469E-01	-4.72208E-02	-4.58781E-02	1.71000E-01	-1.90131E-01	1.00571E-01	-2.04289E-02
5	3.43006E+00	1.71864E-02	1.52386E-02	1.02819E-02	-6.77267E-03	-2.27277E-04	9.20742E-04	-1.70615E-04
6	-7.86820E+00	-9.62610E-03	7.39677E-04	2.03989E-04	-6.48984E-05	4.97891E-06	-7.77507E-08	-8.26887E-09
7	1.62582E+00	-1.60072E-02	1.82955E-03	-4.98787E-04	5.84831E-05	-3.22768E-06	1.19122E-07	-7.79576E-09

(Numerical example 6)

Surface number	Radius of curvature R d	Distance d	Refractive index n _d	Abbe number v _d
1	INF	0.35		
2	9.33932	1.2068	1.60602	57.5
3	-2.06529	0.8427		
4	-1.06161	0.8985	1.58387	30.9
5	-4.94499	0.3928		
6	2.23042	1.96	1.53116	56.0
7	8.2278	0.3		
8	INF	0.43	1.51633	64.1
9	INF	0		

Aspherical coefficient

Surface number	K	A ₄	A ₆	A ₈	A ₁₀	A ₁₂	A ₁₄	A ₁₆
3	1.50629E+01	-4.61001E-02	-5.76962E-02	1.68626E-01	-2.23054E-01	-2.54078E-01	6.27470E-01	-2.68138E-01
4	1.27418E+00	-7.67609E-03	1.00519E-02	-9.23062E-03	5.86144E-03	2.74694E-03	-1.31625E-02	8.23648E-03
5	-8.37673E-01	1.66725E-01	-3.99077E-02	4.14765E-02	-3.81093E-02	-6.22095E-03	1.99685E-02	-5.64656E-03
6	-7.95426E+00	1.24542E-02	3.23980E-02	-7.33465E-03	-1.48070E-03	3.26087E-05	3.01644E-04	-5.01424E-05
7	-8.78752E+00	1.74804E-03	-1.97116E-03	7.53928E-04	-1.05983E-04	8.11665E-07	1.18909E-06	-8.80260E-08
8	-9.66135E-01	-1.64663E-02	2.24248E-03	-4.81394E-04	5.82643E-05	-2.55354E-06	1.06431E-09	-2.05121E-09

(Numerical example 7)

Surface number	Radius of curvature R,d	Distance d	Refractive index n _d	Abbe number v _d
1	INF	0.35		
2	5.96632	1.4353	1.60602	57.5
3	-2.15509	0.7346		
4	-0.95508	0.8608	1.58387	30.9
5	-3.5575	0.3905		
6	2.31838	2.1115	1.53116	56.0
7	7.30243	0.3		
8	INF	0.48	1.51633	64.1
9	INF	0		

A spherical coefficient

Surface number	K	A ₄	A ₆	A ₈	A ₁₀	A ₁₂	A ₁₄	A ₁₆
3	3.31383E+01	-5.25450E-02	-1.68418E-02	-8.09347E-03	3.71994E-03	-3.41435E-02	6.98813E-02	-5.21320E-02
4	9.46842E-01	-5.67226E-03	1.19113E-02	-5.62526E-03	4.54769E-03	-2.72360E-03	1.05920E-03	4.55049E-05
5	-9.39180E-01	1.83795E-01	-1.97922E-02	-7.25830E-03	-2.59880E-03	2.95957E-03	1.60233E-05	-1.45957E-04
6	-9.68356E+00	1.30891E-02	3.37407E-02	-8.19573E-03	-8.59144E-04	2.08738E-04	1.01812E-04	-1.77164E-05
7	-8.09959E+00	-4.08196E-03	3.01222E-04	2.16750E-04	-5.48952E-05	5.57781E-06	-2.08037E-07	-4.00912E-09
8	-2.77554E+00	-1.58978E-02	2.11087E-03	-4.66261E-04	5.64875E-05	-3.18946E-06	1.03448E-07	-4.25283E-09

(Numerical example 8)

Surface number	Radius of curvature R.d	Distance d	Refractive index n _d	Abbe number v _d
1	INF	0.3246		
2	6.4703	1.2495	1.60602	57.5
3	-1.8236	0.733		
4	-0.8238	0.938	1.58387	30.9
5	-2.9321	0.2201		
6	2.00602	1.75	1.52996	55.8
7	5.7801	0.3		
8	INF	0.48	1.51633	64.1
9	INF	0		

Aspherical coefficient

Surface number	K	A ₄	A ₆	A ₈	A ₁₀	A ₁₂	A ₁₄	A ₁₆
3	-7.52521E+00	-4.75316E-02	-3.26435E-02	1.72094E-02	4.94040E-02	-3.12602E-01	4.60163E-01	-2.16665E-01
4	9.54561E-01	-1.00819E-02	3.15306E-02	-2.32362E-02	1.26067E-02	4.52437E-03	-7.33530E-03	3.64479E-03
5	-7.86540E-01	2.79708E-01	-2.30800E-02	-1.18459E-02	-8.33045E-03	1.61864E-02	-3.84045E-03	-4.82111E-04
6	-3.03037E+00	3.19352E-04	7.34520E-02	-2.36939E-02	-1.67352E-03	1.37139E-03	3.73315E-04	-1.49276E-04
7	-9.80269E+00	-6.08300E-03	4.47725E-03	-1.81717E-03	1.58301E-04	1.08348E-04	-3.05909E-05	2.14842E-06
8	-1.09384E+01	-3.18431E-02	1.24005E-02	-4.40912E-03	7.60818E-04	-3.81712E-05	-3.95205E-06	3.48905E-07

(Numerical example 9)

Surface number	Radius of curvature R d	Distance d	Refractive index nd	Abbe number v d
1	INF	0		
2	3.9653	0.8889	1.52996	57.5
3	-1.8248	0.7145		
4	-0.6965	0.5212	1.58387	30.9
5	-1.9538	0.3		
6	1.4842	1.1411	1.52996	55.8
7	5.4462	0.3		
8	INF	0.3	1.51633	64.1
9	INF	0		

Aspherical coefficient

Surface number	K	A4	A6	A8	A10	A12	A14	A16
3	7.30796E+00	-1.11507E-01	-1.16775E-02	-1.80257E-01	6.21600E-01	-3.93257E+00	1.01325E+01	8.81289E+00
4	5.64495E-01	-8.03762E-02	5.99553E-02	-2.23847E-01	2.28892E-01	2.52605E-01	-6.47077E-01	3.04581E-01
5	-1.42200E+00	2.41434E-01	-7.28519E-02	1.83016E-01	-3.94518E-01	5.41646E-01	-4.29104E-01	1.26357E-01
6	-2.86305E+00	2.42264E-02	1.88105E-01	-1.16615E-01	3.62356E-02	-3.56405E-03	-2.37857E-03	-2.03370E-04
7	-7.23765E+00	-4.26307E-03	-3.48968E-03	3.96766E-03	-8.79389E-04	-7.60369E-04	4.00258E-04	-5.48302E-05
8	-2.11172E+00	-3.52522E-02	6.27474E-03	9.74512E-04	-1.43137E-03	2.77429E-04	4.75851E-06	-4.54756E-06

Here, FIGs. 2, 4, 6, 8, 10, 12, 14, 16, and 18 are aberration diagrams corresponding to Numerical examples 1 to 9.

In these aberration diagrams, (a) is a graph showing spherical aberration (SA), (b) is a graph showing astigmatism (AST),
5 and (c) is a graph showing distortion (DIS).

Table 10 shows values for the above numerical examples and numerical values for the conditional expressions.

Table 10. for numerical values of conditional expressions

	Example 1	Example 2	Example 3	Example 4	Example 5	Example 6	Example 7	Example 8	Example 9
	5.013	5.026	4.999	4.995	5.038	5.261	5.174	4.500	3.780
fd	2.574	2.574	2.574	2.589	2.593	2.907	2.799	2.489	2.491
f1d	-2.309	-2.327	-2.328	-2.279	-2.260	-2.531	-2.547	-2.347	-2.188
f2d	5.413	5.502	5.465	5.104	5.110	5.174	5.576	4.995	3.500
f3d	2.170	2.160	2.148	2.192	2.229	2.079	2.032	1.917	1.728
Conditional expression (1)	0.926	0.914	0.915	0.979	0.986	1.017	0.928	0.901	1.080
Conditional expression (2)	-1.536	-1.536	-1.536	-1.527	-1.506	-1.547	-1.734	-1.781	-2.108
Conditional expression (3)	$(r21 + r22) / (r21 - r22)$	-2.030	-2.039	-1.776	-1.739	-1.744	-1.930	-2.063	-1.749
Conditional expression (4)	$(r31 + r32) / (r31 - r32)$	66.926	67.230	67.222	66.840	65.190	66.054	63.506	62.084
Conditional expression (5)	$2 \cdot \omega d$	1.409	1.418	1.415	1.406	1.410	1.440	1.474	1.399
Conditional expression (6)	T/fd	1.947	1.942	1.930	1.943	1.810	1.848	1.808	1.518
Conditional expression (7)	$fd / f1d$	0.403	0.403	0.427	0.399	0.638	0.469	0.560	0.370
Conditional expression (8)	$(r11 + r12) / (r11 - r12)$	30.900	30.900	30.900	30.900	30.900	30.900	30.900	30.900
Conditional expression (9)	V2d	55.800	55.800	55.800	55.800	55.800	55.800	55.800	55.800
Conditional expression (10)	V3d	7.063	7.086	7.088	7.067	7.084	7.450	6.632	5.288
	T								

With reference to FIG. 19, there is described an embodiment for an optical device provided with imaging lenses according to the above embodiments and numerical examples.

5 In FIG. 19, 191 denotes a body of the optical device, such as a digital camera, provided with the imaging lens of the present invention, 192 denotes the imaging lens, 193 denotes an optical finder separately incorporated in the body of the optical device, 194 denotes a strobe light, and 195 denotes a release button.

10 By providing the imaging lens of the present invention with an optical device such as a digital camera, as above, a compact optical device with high optical performance can be achieved.

INDUSTRIAL APPLICABILITY

15 The present invention is effective in providing an imaging lens system having a small number of lenses and with high optical performance, and an optical device such as a digital camera or a mobile telephone terminal provided with a camera, which is compact and of high optical performance, by having the system therein.